



## Installation Spec Sheet:

### Important Notice

Read all instructions before installation. Improper installation may result in product failure and may void warranty. Installer is responsible for final inspection of jobsite conditions prior to installation.

---

### 1. Jobsite Conditions

- Subfloor must be flat, clean, dry, and structurally sound.
  - Subfloor must be flat within 1/8 inch over 6 feet.
  - Moisture levels must be within acceptable industry standards before installation.
  - Any uneven areas must be corrected using a self leveling compound.
  - For glue down installations, a moisture barrier may be required depending on site conditions.
  - Do not install over soft, uneven, or unstable surfaces.
- 

### 2. Acclimation

- Allow flooring to acclimate in the installation area if exposed to extreme hot or cold temperatures prior to installation.
  - Maintain normal living conditions during acclimation.
  - Open cartons and spread planks if possible to allow proper airflow.
- 

### 3. Environmental Requirements

- Install at room temperature between 65°F and 85°F.

- Maintain indoor humidity between 35 percent and 70 percent.
  - Avoid installation in extreme humidity or rapidly changing conditions.
- 

#### **4. Pre Installation Inspection**

- Inspect all planks before installation.
  - Do not install damaged or defective material.
  - Mix planks from multiple boxes to achieve natural color variation.
  - Natural variation in color, texture, and gloss is expected and not considered a defect.
- 

#### **5. Installation Guidelines**

- Do not install under cabinets, islands, or other fixed objects.
  - Leave a 1/4 inch expansion gap around all walls and fixed objects.
  - Do not fasten flooring directly to the subfloor.
  - Stagger end joints for a natural appearance and structural stability.
  - Follow proper installation method based on flooring type (floating, glue down, or click system).
- 

#### **6. Expansion and Movement**

- Flooring will expand and contract with environmental changes.
  - Proper expansion gaps are required at all perimeter walls and fixed objects.
  - Do not restrict movement of flooring in any way.
- 

#### **7. Post Installation**

- Remove debris and clean floor using manufacturer approved cleaning methods.
- Do not drag heavy furniture across newly installed flooring.
- Use protective pads under furniture legs.

---

## **8. Maintenance Guidelines**

- Sweep or vacuum regularly using a hard floor attachment.
- Use damp mop only with approved cleaning solutions.
- Avoid excessive water or steam cleaning unless approved for product type.
- Use mats at entryways to reduce dirt and moisture.

---

## **9. Disclaimer**

Installation must be performed in accordance with these guidelines. Manufacturer is not responsible for failures resulting from improper installation, subfloor conditions, or environmental issues.

Last updated: April 2026